

Android SDK

Release Notes

RFID/Barcode SDK
Ver. 1.17.10



Copyright

Copyright 2017. Aplusetech Co., Ltd. All rights reserved.

Apulsetech is the manufacturer of Apulsetech RFID handheld computers.
This document and related software in this device are protected by international copyright laws.

Any part of this document may not be reproduced, removed or used in any form by any means, without permission in writing from Apulsetech.

The contents in this manual are subject to change without prior notice.

Apulsetech and α811 are registered trademarks of Apulsetech Co., Ltd., all other trademarks and copyrights are property of their respective owners.

The software is provided for user understanding of how to use the device and application development. All software, including firmware, is on a licensed basis.

No right to copy a licensed program in whole or in part is granted, to other devices except as permitted under copyright law.

Apulsetech Co., Ltd.

C-1211, 60, Haan-ro,
Gwangmyeong-si,
Gyeonggi-do,
Republic of Korea

<http://www.apulsetech.com>

Revision History

Change	Date	Description
Ver.1.04.00	2017/11/02	1 st Release
Ver.1.05.00	2017/11/10	SDK v1.05.00 Release
Ver.1.09.00	2018/03/09	SDK v1.09.00 Release
Ver.1.11.00	2018/05/07	SDK v1.11.00 Release
Ver.1.13.00	2018/07/30	SDK v1.13.00 Release
Ver.1.13.01	2018/08/22	SDK v1.13.01 Release
Ver.1.13.02	2018/09/10	SDK v1.13.02 Release
Ver.1.13.03	2018/10/01	SDK v1.13.03 Release
Ver.1.14.00	2018/11/08	SDK v1.14.00 Release
Ver.1.15.00	2018/12/26	SDK v1.15.00 Release
Ver.1.15.01	2019/01/14	SDK v1.15.01 Release
Ver.1.16.00	2019/04/05	SDK v1.16.00 Release
Ver.1.16.01	2019/06/10	SDK v1.16.01 Release
Ver.1.16.02	2019/08/13	SDK v1.16.02 Release
Ver.1.16.03	2019/09/27	SDK v1.16.03 Release
Ver.1.17.00	2019/12/25	SDK v1.17.00 Release
Ver.1.17.10	2020/02/24	SDK v1.17.10 Release

Table of Contents

1.	Requirements.....	5
	■ Supported Operating Systems	5
	■ Supported Hardware	5
	■ Supported IDE Environments.....	5
2.	Release History	6
	■ V1.17.10.....	6
	■ V1.17.00.....	6
	■ V1.16.03.....	7
	■ V1.16.02.....	7
	■ V1.16.01.....	8
	■ V1.16.00.....	8
	■ V1.15.01.....	9
	■ V1.15.00.....	9
	■ V1.14.00.....	11
	■ V1.13.03.....	12
	■ V1.13.02.....	13
	■ V1.13.01.....	13
	■ V1.13.00.....	14
	■ V1.11.00.....	14
	■ V1.09.00.....	15
	■ V1.05.00.....	15
	■ V1.04.00.....	16
3.	Customer Support.....	17
1)	Technical Support	17
2)	Feedback	17

1. Requirements

■ Supported Operating Systems

The requirements for APULSETECH Android SDK are as shown below.

- ① Windows 7/8/10 or newer recommended
- ② Ubuntu Linux 14.04 LTS or newer recommended
- ③ OSX

■ Supported Hardware

- ① α811 Android handheld reader(local execution)
- ② ARM 32bit v7a and 64bit v8a architecture-based Android devices with 5.0 or above(remote connection support with α711 and α811)

■ Supported IDE Environments.

- ① Eclipse Neon for Android Application Developers with Android SDK
- ② Android Studio 3.5 or newer recommended

2. Release History

For details about the changes in each release, please refer to the summary of version history.

■ V1.17.10

New Features

[Barcode]

[RFD]

- Added EM Microelectronics sensor tag support.

[Common]

- Added barcode scanner and RFD reader connection switching support between local and remote.
- Added contentProvider support to query the execution state of barcode scanner and RFD reader in local and remote.

Issue Fixes

[Barcode]

[RFD]

- Resolved the overflow issue of starting pointer value of the read command in the remote connection (sensor reading issue of Farsense tag).

[Common]

- Minor issue fixes.

■ V1.17.00

New Features

[Barcode]

[RFD]

- Added 2 bytes block write support (NXP tag).
- Added the inventory start event for a remote device.

[Common]

- Added USB bulk connection (accessory mode) support.
- Added USB HD mode support.

Issue Fixes

[Barcode]

- Changed the file path of Excel export. /sdcard/BarcodeData/BarcodeList_YYMMDDhhmmss.xls

[RFD]

- Fixed some structural errors of remote packets.
- Changed the file path of Excel export. /sdcard/TagData/TagList_YYMMDDhhmmss.xls.

[Common]

- Resolved the Bluetooth device scan issue after waking up from sleep.
- Fixed minor errors and improved performance.
- Support additional remote connection interfaces.
- Supported interfaces for remote connection, refer to the below table.

		Remote Manager	Client OS		
			Android	Windows	iOS
Serial		O	X	O	X
USB to Serial		O	O ¹	O	X
USB	Remote	O	O	To be supported ³	TBD
	HD	O	O	To be supported ²	TBD
Bluetooth	BLE	O	O	To be supported ²	To be supported
	SPP(Socket)	O	O	O	X
WiFi	Socket	O	O	O	To be supported
	P2P(Direct) + Socket	O	△ Search only. Connection to be supported	O	X

* Remark

1. Supported cables refer to the below table.
2. Compatibility problem of BLE connection control between Android and Windows.
3. To be supported by Windows SDK.

■ V1.16.03

New Features

[Barcode]

[RFD]

- Added LED tag (N1EDL chip base) support.
- Added tag trace function support to the demo app.
- Added tag block access function support to the demo app.
- Added DRM (Dense Reader Mode) setting support.
- Added tag selection support to Fujitsu APs.

[Common]

Issue Fixes

[Barcode]

- Updated 2D barcode libraries.

[RFD]

- Fixed the packet parameter error for some remote commands.

[Common]

■ V1.16.02

New Features

[Barcode]

[RFD]

[Common]

- Added α711 remote connection support.

Issue Fixes

[Barcode]

[RFD]

- Fixed the calculation overflow issue related to a few functions.
- Added extra mac error codes for error reporting.

[Common]

■ V1.16.01

New Features

[Barcode]

[RFD]

- Added sensor data to excel export support in the demo app.

[Common]

Issue Fixes

[Barcode]

[RFD]

[Common]

- Changed the file path of excel export in the demo app.
- Updated SDK documents.

■ V1.16.00

New Features

[Barcode]

[RFD]

- Added Farsense sensor tag support.
 - Supported model list

Model	Functions	Tested
Stellar-R	EPC + PTL LED indicator	X
Kineo-RM	EPC + Orientation + PTL LED indicator	X
RMeter-RM	EPC + Resistance + PTL LED indicator	X

Fenix-Vortex-RM	EPC + Temperature + Pressure + PTL LED indicator	X
Fenix-RM	EPC + Temperature + PTL LED indicator	X
Hygro-Fenix-RM	EPC + Humidity + Temperature + PTL LED indicator	X
X5R	EPC + Switch State	X
Titan-R	EPC + Relay State	X
Magneto-RM	EPC + Magnetic + PTL LED indicator	X
CMeter-RM	EPC + Charge + PTL LED indicator	X
Cyclon-RM	EPC + Temperature + Pressure + PTL LED indicator	O

- Added 'Energizing Carrier' option in the demo's read/write function.

[Common]

Issue Fixes

[Barcode]

[RFD]

[Common]

- Replaced audio effect resources.

■ V1.15.01

New Features

[Barcode]

[RFD]

[Common]

Issue Fixes

[Barcode]

[RFD]

[Common]

- Improved multi-connection handling of BLE remote connection.
- Improved error handling of remote connection.
- Improved touch control of expanding and collapse for operation setting regions in the demo app.

■ V1.15.00

New Features

[Barcode]

[RFD]

[Common]

- Added heartbeat packet ping and timeout handling for remote connection.
- Added excel export for barcode and tag data.
- Added multi language support for demo apps.
 - Currently supported languages
English, Korean, Chinese, Japanese.
 - The remaining resources of barcode symbology configuration will be translated in the future release.
- Support additional remote connection interfaces.
 - Supported interfaces for remote connection, refer to the below table.

		Remote Manager	Client OS		
			Android	Windows	iOS
Serial		O	X	O	X
USB to Serial		O	O ¹	O	X
USB	Remote	To be supported ³	To be supported ³	To be supported ³	X
	HD	To be supported ⁴	To be supported ⁴	To be supported ⁴	X
Bluetooth	BLE	O	O	To be supported ²	To be supported
	SPP(Socket)	O	O	O	X
WiFi	Socket	O	O	O	To be supported
	P2P(Direct) + Socket	O	△ Search only. Connection to be supported	O	X

* Remark

- Supported cables refer to the below table.
- Compatibility problem of BLE connection control between Android and Windows.
- Available after the device driver is supported.

- Multiple connection support for device scan and query¹.

		Multiple clients → Device	Multiple devices → Client
Serial		X ²	X ²
USB to Serial		X ²	X ²
Native USB		X ²	X ²
Bluetooth	BLE	O	O
	SPP(Socket)	O	O
WiFi	Socket	O	O
	P2P(Direct) + Socket	O	O

* Remark

- Multiple connections are only available for device scan and query.
The multiple connections to function modules including barcode and RFD are not allowed.
- The single connection only due to its H/W interface limitation.

- Supported baud rates for USB to Serial interface, refer to the below table.

	Supported chip	Supported bps
FTD	FT231X series	TBD

	FT232R	TBD
Silicon Labs	CP210X series	TBD
Prolific	PL2303	115200, 230400, 460800, 921600
QinHeng	CH340	TBD

Issue Fixes

[Barcode]

- Updated 2D barcode libraries.

[RFD]

[Common]

- Improved error control of the remote connection.
- Changed the default timeout value of remote connection to 40s the same as a heartbeat.
→ In remote scanner settings, select and test proper timeout value.
- Improved big data processing performance of demo apps.
- Applied miscellaneous bug fixes and improvements.

■ V1.14.00

New Features

[Barcode]

[RFD]

- Added Fujitsu tag support.
- Support extra inventory information including phase, channel and Monza M4 FastD.
- Support library level filtering for inventory data.
- Support remaining data loading from a remote device.
- Demo app can display extra inventory information including phase, channel and Monza M4 FastD.

[Common]

- Added sound volume control support.
- Added loading screen for initialization in the demo app.
- The setting region can be hidden or shown by demand in the demo app.
- Added data sort support in the demo app.
- HD demo also supports remote connection with clipboard copy/paste.
- Added HD clipboard demo app.
- Support additional remote connection interfaces.
- Supported interfaces for remote connection, refer to the below table.

		Remote Manager	Client OS		
			Android	Windows	iOS
Serial		O	X	O	X
USB to Serial		To be supported	O ¹	O	X
Bluetooth	BLE	O	O	To be supported	To be supported
	SPP(Socket)	O	O	To be supported	X
WiFi	Socket	O	O	To be supported	To be supported
	P2P(Direct) + Socket	O	△ Search only. Connection	To be supported	X

			to be supported		
--	--	--	-----------------	--	--

* Remark

1. Supported cables refer to the below table.

- multiple connection support for device scan and query¹.

		Multiple clients → Device	Multiple devices → Client
Serial		X ²	X ²
USB to Serial		X ²	X ²
Bluetooth	BLE	△ Supported. But needs improvements.	O
	SPP(Socket)	To be supported	O
WiFi	Socket	To be supported	O
	P2P(Direct) + Socket	X	△ Search only. Connection to be supported.

* Remark

1. Multiple connections are only available for device scan and query.
The multiple connections to function modules including barcode and RFD are not allowed.
2. The single connection only due to its H/W interface limitation.

- Supported baud rates for USB to Serial interface, refer to the below table.

	Supported chip	Supported bps
FTD	FT231X series	TBD
	FT232R	TBD
Silicon Labs	CP210X series	TBD
Prolific	PL2303	115200, 230400, 460800, 921600
QinHeng	CH340	TBD

Issue Fixes

[Barcode]

- Updated 2D barcode libraries.

[RFD]

- Disabled ch.0 in the Korea region.
- Resolved the sensor data refresh issue in the sensor tag inventory screen.
- Revised sensor data display for RFMicron Magunus S1 and S2 sensor tags.

[Common]

- Improved error control of the remote connection.
- Improved search and connection stability of the remote device.
- Fixed binding leaks of HD services.
- Applied miscellaneous bug fixes and improvements.

■ V1.13.03

New Features

[Barcode]

- Added nverse 1D barcode setting.

[RFD]

- Added RFMicron sensor tag support.
- Added RFMicron sensor tag support in the demo app.

[Common]

Issue Fixes

[Barcode]

[RFD]

- Fixed packet parsing errors.

[Common]

■ V1.13.02

New Features

[Barcode]

[RFD]

[Common]

Issue Fixes

[Barcode]

[RFD]

- Added force reset before connecting the RFD module.
- Adjusted max RF power from 33dBm to 30dBm.
- Added high baudrate support for module serial connection (**OS v1.03 or higher**).
Before: 115200, 230400
Current: 115200, 230400, **460800, 921600**
- Removed regulatory region information from the main screen of the demo app.
- Resolved the button link mismatch issue on firmware update dialog.

[Common]

- Updated audio resources for demo apps.

■ V1.13.01

New Features

[Barcode]

[RFD]

[Common]

Issue Fixes

[Barcode]

[RFD]

- Revised BlockPermalock() AP.

[Common]

- Updated Remote Manager app.

■ **V1.13.00**

New Features

[Barcode]

[RFD]

[Common]

- Added trigger control option to demo app.
- Added multi-event listener support.

Issue Fixes

[Barcode]

- Removed vibrator setting option from the barcode demo app.

[RFD]

- Improved tab widget UI for easy visibility .
- Fixed NULL channel information issue.
- Revised application parameter condition of selection criteria.
- Added and removed some APs.
 - Added: isOperationRunning(), stopOperation()
 - Removed: isInventorying(), stopInventory()
- Adjusted response timeout and improved operation abort control.

[Common]

- Revised settings not to be allowed to change while the operation is running
- Fixed some crash issues of the demo app.
- Resolved a remote response parsing error.

■ **V1.11.00**

New Features

[Barcode]

[RFD]

[Common]

- Added remote device connection support through serial, BLE and WiFi for a barcode scanner and RF D reader.

Issue Fixes

[Barcode]

- Fixed the parameter handling issues of symbology settings.

[RFD]

- Fixed serial reconnection fail issue while changing baudrate.

[Common]

- Improved handling of some GU widget controls in demo apps.
- Added extra improvements and fixes.

■ V1.09.00

New Features

[Barcode]

- Added handsfree and auto mode support.

[RFD]

- Added some new APs.
isInventorying(), getAccessTimeout(), setAccessTimeout(), getRegulatoryRegion(), getInventorySelectionTarget(), setInventorySelectionTarget(), getBaudrate(), setBaudrate()
- Added nvSelectionTarget, Selection constants.

[Common]

- Renewed demo apps.

Issue Fixes

[Barcode]

- Fixed random crash issues while executing scanner operations.

[RFD]

- Resolved wrong regulatory region display issue.
- Resolved some operating issues related to execution time.
- Renamed some APs

[Common]

■ V1.05.00

New Features

Issue Fixes

- Changed some RFD global index order as shown below.

Before	After
--------	-------

...		...	
AUSTRALIA	= 3	CHINA	= 3
BANGLADESH	= 4	BANGLADESH	= 4
BRAZIL	= 5	BRAZIL	= 5
BRUNEI	= 6	BRUNEI	= 6
CHINA	= 7	AUSTRALIA	= 7
HONGKONG	= 8	JAPAN_1	= 8
INDIA	= 9	JAPAN_2	= 9
INDONESIA	= 10	HONGKONG	= 10
IRAN	= 11	INDIA	= 11
ISRAEL	= 12	INDONESIA	= 12
JAPAN_1	= 13	IRAN	= 13
JAPAN_2	= 14	ISRAEL	= 14
...		...	

- Resolved the value reset issue of barcode settings which is previously configured.

■ V1.04.00

New Features

- First release.

Issue Fixes

3. Customer Support

1) Technical Support

Please visit the APULSETECH website for technical support. You can report your issues and get their answers. Also, you can get all the latest information and updates for products and software.

2) Feedback

Please send us your feedback about APULESTECH products.